

REMARKS

Claims 1-7 have been canceled. New claims 8-14 have been added. Thus, claims 8-14 are presented for examination. Applicant respectfully requests allowance of the present application in view of the foregoing amendments.

The amendments are not made for purposes of patentability.


A substitute specification incorporating the changes in this preliminary amendment is provided with this application. No new matter has been added by way of the substitute specification.

Conclusion

The commissioner is hereby authorized to charge any appropriate fees due in connection with this paper, including the fees specified in 37 C.F.R. §§ 1.16 (c), 1.17(a)(1) and 1.20(d), or credit any overpayments to Deposit Account No. 19-2179.

Respectfully submitted,

Dated: 12/17/05

By: 
John P. Musone
Registration No: 44,961
(407) 736-6449

Siemens Corporation
Intellectual Property Department
170 Wood Avenue South
Iselin, New Jersey 08830

Description

UNIDIRECTIONAL LIGHTING DEVICE FOR ILLUMINATING OBJECTS AND/OR FOR MARKING LANES, PREFERABLY IN THE AIRPORT AREA

5

CROSS REFERENCE TO RELATED APPLICATIONS

[001] This application is the US National Stage of International Application No. PCT/EP2004/006623, filed June 18, 2004 and claims the benefit thereof. The International Application claims the benefits of German application No. 10329496.1, filed June 30, 2003.

10 both applications are incorporated by reference herein in their entirety

FIELD OF INVENTION

[002] The invention relates to a unidirectional lighting device for illuminating objects and/or for marking lanes, preferably in the airport area, according to the preamble of Claim 1.

15

SUMMARY OF THE INVENTION

[003] The publication entitled "Approach, Threshold Runway End High Intensity Elevated Light" published by ADB, a Siemens company, 4/11.97, order number E10001-T95-A61-V1-7600 discloses a unidirectional lighting device for marking the approach and threshold area as well as the takeoff and landing path limits of airports. The lighting device comprises a main body having an external housing which can be erected and fastened on the ground, a post or a mast. The lighting device also comprises optical components, specifically a light source, a reflector and a front glass for producing a parallel light beam.

20

[004] A change of the light source in this known lighting device is possible without tools, but can only be carried out at the erection location in the field via a door which is arranged on the rear panel of the external housing. In order to perform workshop maintenance of the optical components, the complete lighting device must be taken down, transported to the workshop and then aligned again after re-erection. The main body of the lighting device consists of a cast aluminum external housing and noble metal parts, and corrosion resistance is therefore difficult to achieve and only partly possible.

25

30

[005] The invention therefore addresses the problem of overcoming the aforementioned disadvantages of the prior art in the case of a lighting device of the type cited at the beginning, in particular of providing a lighting device whose maintenance is simplified.

35

[006] According to the invention, the problem is solved by a lighting device of the type in

question, said lighting device having the features described ~~herein in the characterizing part~~
of Claim 1. As a result of the combination of the partly metallic optical components in a
separate optics module which can be installed in the main body of the lighting device, and as
a result of the construction of large parts of the external housing of the main body from non-
5 metallic materials, a lower overall weight of the claimed lighting device is achieved, thereby
making it easier to replace in the field. As a result of using non-metallic materials for the
external housing, in particular a higher corrosion-resistance is achieved for a lighting device
in accordance with the invention. Furthermore, the embodiment of the overall lighting device
can be smaller, thereby reducing the wind sensitivity and therefore the danger of breakage.
10 Consequently, it is possible to fasten a lighting device according to the invention onto higher
masts than in the prior art. The non-metallic and therefore non-conducting construction of the
external housing allows the insulated fastening of a drive amplifier of the lighting device,
thereby allowing the reliable transmission of triggering signals even over cable lengths up to
250 m. The plastic construction of the external housing provides for greater flexibility in layout
15 and production and for better frictional behavior. Due to the limited heat conductivity and
electrical conductivity of non-metallic materials, there are fewer problems taking hold of and
handling an external housing of corresponding construction.

[007] In an advantageous embodiment of the claimed lighting device, the optics module is
20 rotatably linked to the main body via pivoting means. As a result of this, the lighting device
can be opened on site, i.e. at the erection location in the field, e.g. by swinging it open,
thereby allowing unimpeded access to the built-in parts and in particular the optical
components. It is therefore easy to undertake a replacement of the light source in situ, for
example.

[008] In a preferred embodiment of the invention, the optics module is designed to be
removable from the main body of the lighting device. The separability of the optics module
means that it can be maintained in the workshop without the need to take down the complete
lighting device. For example, the pivoting means can be designed in such a way that the
30 optics module can be detached from the main body without using tools.

[009] In a preferred embodiment of the claimed lighting device, an upper part of the main
body, which upper part accommodates the optics module, is designed relative to a lower part
of the main body, which lower part carries the upper part, such that it can be tilted about a
35 horizontal axis and rotated about a vertical axis. With the aid of this design, it is possible to
perform an orientation of the optical axis of the parallel light beam which is emitted by the
optics module. It is particularly advantageous that, when a tilt and rotate position has been

set, the upper part does not change in relation to the lower part if the optics module is swung open or removed. Consequently, a time-consuming readjustment of the lighting device is no longer required if a lamp is changed or in the case of maintenance tasks.

5 **[0010]** In a preferred configuration of the claimed lighting device, adjusting means are provided for setting and fixing the tilt position of the upper part relative to the lower part of the main body. For this purpose, provision is made for a mechanism having two adjustment screws which engage in a diametrically opposed manner and fix the upper part in a set tilt position. In order to change the tilt position, one of the two adjustment screws is unscrewed
10 by the same amount as the other adjustment screw is tightened, wherein the upper part is tilted about the horizontal axis of rotation. As a result of this adjustment mechanism, it is possible to achieve a very accurate orientation of the angle of the optical axis relative to the vertical. The axial position of an adjustment screw is preferably fixed by a lock nut which engages in the housing. This ensures a locking of the tilt position of the upper part relative to
15 the lower part of the main body of the lighting device according to the invention.

[0011] In a further preferred configuration of the invention, locking means are provided for fixing the rotational position of the upper part relative to the lower part of the main body. As a result, it is likewise possible to fix a set orientation of the optical axis of the light beam in the
20 form of an azimuthal angle relative to a base position.

[0012] The non-metallic external housing of the main body is preferably designed as a plastic part, in particular an injection molded part. In this way, stable non-metallic external housings
25 can be provided at low manufacturing cost for lighting devices in accordance with the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

30 **[0013]** Further properties and advantages of the claimed lighting device are derived from the following description of the drawings, in which:

[0014] FIG 1 schematically illustrates a partly cutaway side view of a lighting device according to the invention;
35

[0015] FIG 2 schematically illustrates a lighting device according to the invention, including an optics module in a closed state;

[0016] FIG 3 schematically illustrates a lighting device according to the invention, including an optics module in a swung open state;

5 **[0017]** FIG 4 schematically illustrates a lighting device according to the invention, including an optics module in a separated state.

DETAILED DESCRIPTION OF INVENTION

10

[0018] As shown in FIG 1, a lighting device 10 according to the invention has a main body 20 for erecting and fastening the lighting device 10 and an optics module 30 for generating a light beam along an optical axis O. The main body 20 is enveloped by a non-metallic external housing 22 and essentially comprises an upper part 24, an intermediate part 25 and a lower part 26. The optics module 30 is laterally attached to the upper part 24 of the main body 20, which upper part also contains electrical components for controlling and operating the optics module 30. The upper part 24 is supported on the intermediate part 25 by means of a hinge bolt which is aligned longitudinally along a horizontal axis of rotation H, and is therefore tiltably positioned about the axis of rotation H which extends perpendicularly to the page plane. The intermediate part 25 of the main body 20 is rotatably positioned on the lower part 26 about a vertical axis V. For this purpose, the intermediate part 25 is centered over a bearing journal 27 in the supporting pillar 28 of the lower part 26. The assembly comprising intermediate part 25, upper part 24 and optics module 30 is therefore rotatably configured about the vertical axis of rotation V relative to the non-rotatable lower part 26. A radial necking 29 is formed in the supporting pillar 28 of the lower part 26, providing a predetermined breaking point if the claimed lighting device 10 is positioned on the ground.

20

25

30

[0019] The optics module 30 has a housing 37 which is adapted to the lateral cross-section of the external housing 22 and in which are arranged a parabolic reflector 34 and a light source 32 in the form of a halogen lamp, said light source being approximately central. The housing 37 is covered on a front side, which is provided for the issue of light, by a front glass 36 that is fastened to the housing 37 by means of a front ring 39 which runs around the circumference of the front glass 36. Depending on the desired color of the issuing light beam, the front glass 36 is clear or colored red or green.

35

[0020] The optics module 30 is rotatably linked to the upper part 24 of the main body 20 via pivoting means 40 having the form of a hinge. In this way, the optics module 30 can be

swung downwards for changing the light source 32 or for other maintenance tasks, in order to gain access to the rear panel of the housing 37 or to the interior of the housing 22. Upon completion of the tasks, the optics module 30 is swung upwards again until a seal 38 which surrounds the housing 37 is flush with the external housing 22 of the upper part 24 and the
5 spring keeper 23 in an engaged locking position in the rear panel of the housing 37 secures the optics module 30. In order to swing open again, the spring force of the keeper 23 must be overcome.

[0021] At the erection location, whether embedded in the ground via the supporting pillar 28
10 or supported on a post or mast above the ground, the alignment of the optical axis O must be adjusted. The polar and azimuthal angles can be set via the horizontal or vertical axes of rotation H or V. In order to set the polar angle, i.e. the inclination of the optical axis O relative to the vertical, adjusting means 50 are provided in the form of a pair of adjusting screws which are screwed into the intermediate part 25 diagonally from below. The ends of the
15 adjusting screws touch surfaces of the upper part 24 which is arranged rotatably about the horizontal axis of rotation H, wherein only the right-hand adjusting screw of the two adjusting screws is illustrated in FIG 1. In this case, it is only possible to screw in one of the adjustment screws if the other adjustment screw is unscrewed. The adjusting means 50 which are designed in this way allow a very precise adjustment of the tilt position of the upper part 24
20 relative to the lower part 26 of the main body 20. Once it has been set, a tilt position can be locked by lock nuts. The setting of the azimuthal angle, i.e. the orientation relative to a celestial direction, is achieved by rotating the assembly which is supported by the lower part 26 about the vertical axis of rotation V. In order to fix a set rotation position, provision is made for locking means 60 in the form of a clamping ring, wherein said locking means grip the
25 external housing of the intermediate part 25 and squeeze it against the supporting pillar 28 when tightened.

[0022] The claimed lighting device 10 device is used e.g. as a signaling entity for air navigation or for other traffic areas, in particular for the approach area, the threshold
30 markings and end markings of landing paths at airports. The non-metallic plastic construction of the external housing 22 of the main body 20 results in a lower weight, thereby facilitating the replacement in the field of a lighting device 10 according to the invention, and greater corrosion resistance, thereby extending the service life of the lighting device 10. This design also allows smaller dimensions, resulting in reduced wind sensitivity, thereby improving the
35 fragility of a lighting device 10 according to the invention. Furthermore, it is possible to attach the lighting device 10 having smaller overall dimensions to higher fastening masts. The tilt mechanism is situated in the interior of the main body 20 in the case of a lighting device 10

according to the invention, and is therefore attached in a protected manner. The same main body 20 is suitable for optics modules operating as both continuous and flashing lights. The lighting device 10 is protected by seals against ingress of water or dust. Power cables are entirely encased within the main body 20 and are therefore likewise protected.

5

[0023] An essential advantage of the lighting device 10 according to the invention relates to the increased ease of maintenance and is illustrated subsequently in FIG 2 to FIG 4. FIG 2 shows a lighting device 10 having a main body 20 to which the optics module 30 is linked via pivoting means 40, wherein the optics module 30 is swung upwards and fixed to the main
10 body 20 and is therefore in an operating position. In order to change the light source 32, for example, the optics module 30 is pivoted downwards as per the direction arrow D such that free access exists to the rear panel of the optics module 30. Following replacement of the light source or following other maintenance tasks which can be performed on site, the optics module 30 is swung upwards via the pivoting means 40 which are designed as a hinge, until
15 the keeper 23 is snapped into its locking position. If a complete replacement of the optics module 30 is required or if more extensive maintenance of the optics module is required in the workshop, the optics module 30 can be entirely detached from the main body 20 as illustrated in FIG 4. This can be achieved by removing the pins which are arranged at retaining plates of the optics module 30 from a voluted supporting plate of the main body 20,
20 without the need for a disassembly tool.

ClaimsWhat is Claimed is:

1. ~~A unidirectional lighting device (10) for illuminating objects and/or for marking lanes, preferably in the airport area, having a main body (20) for erecting and fastening the lighting device (10), said main body including an external housing (22), and having optical components for generating a light beam along an optical axis (O), said optical components including at least a light source (32), a reflector (34) and a front glass (36), characterized in that the external housing (22) is non-metallic and the optical components (32, 34, 36) are arranged in an optics module (30) which can be attached to the main body (20).~~
2. ~~The lighting device as claimed in Claim 1, characterized in that the optics module (30) is rotatably (D) linked to the main body (20) via pivoting means (40).~~
3. ~~The lighting device as claimed in Claim 1 or 2, characterized in that the optics module (30) can be separated from the main body (20).~~
4. ~~The lighting device as claimed in one of the Claims 1 to 3, characterized in that an upper part (24) of the main body (20), which upper part includes the optics module (30), can be tilted about a horizontal axis (H) and rotated about a vertical axis (V) in relation to a lower part (26) of the main body (20), which lower part supports said upper part (24).~~
5. ~~The lighting device as claimed in Claim 4, characterized in that adjusting means (50) are provided for adjusting and fixing the tilt position of the upper part (24) relative to the lower part (26) of the main body (20).~~
6. ~~The adjusting means as claimed in Claim 4 or 5, characterized in that locking means (60) are provided for fixing the rotational position of the upper part (24) relative to the lower part (26) of the main body (20).~~
7. ~~The lighting device as claimed in one of the Claims 1 to 6, characterized in that the non-metallic external housing (22) of the main body (20) is designed as a plastic part, preferably an injection molded part.~~
8. A unidirectional lighting device for illuminating objects and/or for marking lanes,

preferably in the airport area, having:

a main body for erecting and fastening the lighting device, said main body including an external housing, and having optical components for generating a light beam along an optical axis, the optical components including at least a light source, a reflector and a front glass,
5 wherein the optical components are arranged in an optics module which can be attached to the main body, the external housing is non-metallic and that the optics module is rotatably linked to the main body via a pivoting means, wherein the optics module can be swung between an operating position in which it is fixed to the main body, and an opened maintenance position giving unimpeded access to the optical components.

10 9. The lighting device as claimed in Claim 8, wherein the optics module is separatable from the main body.

15 10. The lighting device as claimed in Claim 8, wherein the main body has an upper part that includes the optics module, with the upper part being fixed to a lower part in tiltable relation about a horizontal axis and rotatable about a vertical axis in relation to the lower part of the main body, wherein the lower part supports the upper part.

20 11 The lighting device as claimed in Claim 10, further having an adjusting device for adjusting and fixing the tilt position of the upper part relative to the lower part of the main body.

25 12. The adjusting means as claimed in Claim 10, further having a locking device for fixing the rotational position of the upper part relative to the lower part of the main body.

13. The lighting device as claimed in Claims 8, wherein the non-metallic external housing of the main body is consisting of suitable form of plastic.

30 14. The lighting device as claimed in Claim 13 wherein the main body is formed using the process of injection molding.

ABSTRACT

The invention relates to a unidirectional lighting device for illuminating objects and/or for marking lanes, preferably in the airport area. Said device comprises a base having an external housing for placing and fastening the lighting device and optical components which
5 comprise at least one light source, one reflector and one front glass and which produce a light beam along an optical axis. The external housing does not consist of metal and the optical components are disposed in an optical module to be added on to the base, thereby
providing a lighting device which is easy to maintain.

10